

<b>The new Arteon 2.0 TSI 4MOTION</b>		<b>206 kW (280 PS)</b>
<b>Engine, electrics</b>		
Type of engine		4-cyl. petrol engine TSI
Effective displacement	cm <sup>3</sup>	1,984
Valves per cylinder		4
Injection / Charge		Direct injection / Turbocharger
Power output		206 (280) kW (PS) 5,100 - 6,500 at rpm
Max. torque	Nm at rpm	350 / 1,700 - 5,600
Alternator (A)		140
<b>Driving performance data</b>		
Acceleration 0 - 80/100 km/h	s	3.7 / 5.6
Top speed	km/h	250
<b>Fuel consumption</b>		
Fuel type		Premium plus min. 98 RON
Urban	l/100km	9.2
Extra-urban	l/100km	6.1
Combined cycle	l/100km	7.3
CO2 emissions, combined	g/km	
NOx	mg/km	16.2
Particulates	mg/km	0.5200
Non-methane hydrocarbons (NMHC)	mg/km	34.7
Efficiency label		C
Exhaust emissions classification		Euro 6 W
<b>Power transmission</b>		
Gearbox		Seven-speed dual-clutch gearbox (DSG), 4MOTION four-wheel drive
<b>Exterior dimensions</b>		
Number of doors		4
Length	mm	4,862
Width	mm	1,871
Height to	mm	1,450
Height with boot lid open	mm	2,172
Length with towing bracket (maximum length)	mm	4,952
Width with door mirrors	mm	2,127
Wheelbase	mm	2,837
Track, front min.	mm	1,587
Track, front max.	mm	1,591
Track, rear min.	mm	1,577
Track, rear max.	mm	1,581
Ground clearance	mm	138
Turning circle	m	11.9
<b>Interior dimensions</b>		
Number of seats		5
Head area: 1st seat row / 2nd seat row / 3rd seat row	mm	1,008 / 940
Head area (glass sunroof): 1st seat row / 2nd seat row / 3rd seat row	mm	975 / 940
Interior width: 1st seat row / 2nd seat row / 3rd seat row	mm	1,500 / 1,481 /
<b>Luggage compartment</b>		
Length, rear seat raised/folded down	mm	1,181 / 2,092
Luggage volume	l	563 - 1,557 1)
<b>Weights</b>		
Kerb weight (EU, incl. 75 kg driver)	kg	1,716
Permitted gross weight	kg	2,240
Payload from / to	kg	465 - 599
Permitted axle load, front/rear	kg	1,130 / 1,160
Allowable trailer weight up to 12% / 8% grade, braked	kg	2,200 / 2,200
Allowable trailer weight, unbraked	kg	750
Permitted drawbar weight/roof load	kg	90 / 100
<b>Capacities</b>		
Fuel tank	l	66

1) Measurement according to ISO 3832